


GMO(P10.4/P15.6/P25/P31.25)

FEATURES

- High Transparency
- Can be installed into a cubic shape
- Ultra light and slim
- Front&back maintenance
- Optional smart lock system, easy installation
- Curve cabinet available
- High brightness
- Can be used in both outdoor fixed and rental projects



SPECIFICATIONS

Product	P10.42	P15.6(SMD)	P15.6(DIP)	P15.6^5	P15.671.25
Pitch	10.42mm	15.6mm	15.6mm	H25°V15.6mm	H31.25°V15.6mm
Density (pixels/m2)	9216	4096	4096	2560	2048
LED Type	SMD2727	SMD2727	DIP346	DIP346	DIP346
Brightness	5500~6000nits	7500nits	8500 nits	7500nits	7500nits
Scan Method	1/3	Static	Static	Static	Static
Cabinet Size	500*1000mm				
Module Size	250*500mm				
Cabinet Material	Diecasting Aluminum				
Cabinet Weight	9.5KG	9KG	10.5KG	10.5KG	10KG
Protection Level	IP65				
Cabinet Maintenance	Front &Rear Service				
Transparency	20%	30%	30%	45%	55%
Max Power Consumption	800w/m2	800w/m2	500w/m2	400w/m2	350w/m2
Average Power Consumption	280w/m2	280w/m2	150w/m2	140w/m2	120w/m2
Refresh Rate (Hz)	2880H3840HZ				
Grey Scale	16 bit				
Viewing Angle	H140°, V140°		H140°, V70°		
Voltage	AC100~240V(50-63Hz)				
Working Temperature	-30°C- +65°C				
Working Humidity	10%-90%RH				
Color Temperature	6500-9500K				
Certifications	EMC/CE/ROHS/CCC/FCC/ISO/BIS				