

Temperature Sensing Crystals Unit YSX221TS




Applications

- Mobile Communications

Features

- Excellent Reliability Characteristics Such as Heat and Mechanical Shock

- Pb-free and Satisfy ROHS Requirements



Specifications (规格参数)

Item / Type	Specifications
Output Frequency Range 额定频率范围	12 ~ 54MHz
Operating Temperature Range 工作温度	-30 ~ +85°C, or specify
Storage Temperature Range 储存温度	-40 ~ +85°C
Frequency Tolerance (at 25°C) 频率偏差	±10ppm, or specify
Frequency Stability Over Operating Temperature Range 频率-温度特性	±10ppm, or specify
Shunt Capacitance (C0) 静态电容	3pF Max
Drive Level 激励电平	1~200μW (50μW typical)
Load Capacitance 负载电容	8pF, 10pF, 12pF, or specify
Aging (at 25°C) 老化率	± 3 ppm / first year Max
Thermistor Resistance (at 25°C) 热敏电阻	100KΩ ±1%
Thermistor B-constant (25~50°C) 热敏电阻B常数	4250KΩ±1%

Equivalent Series Resistance (等效串联电阻 (ESR))

Frequency Range	ESR
12 ~ 13MHz	150Ω Max
14 ~ 30MHz	100Ω Max
30 ~ 54MHz	60Ω Max

Dimensions and Recommended Land Pattern (外观尺寸及推荐焊盘)

Dimensions (Unit: mm)	Recommended Land Pattern (Unit: mm)										
Top View Side View Bottom View	Recommended soldering <table border="1"> <thead> <tr> <th>Pin</th><th>FUNCTION</th></tr> </thead> <tbody> <tr> <td>#1</td><td>XTAL Terminal 1</td></tr> <tr> <td>#2</td><td>Thermistor Terminal 2</td></tr> <tr> <td>#3</td><td>XTAL Terminal 2</td></tr> <tr> <td>#4</td><td>Thermistor Terminal 1</td></tr> </tbody> </table>	Pin	FUNCTION	#1	XTAL Terminal 1	#2	Thermistor Terminal 2	#3	XTAL Terminal 2	#4	Thermistor Terminal 1
Pin	FUNCTION										
#1	XTAL Terminal 1										
#2	Thermistor Terminal 2										
#3	XTAL Terminal 2										
#4	Thermistor Terminal 1										