

Temperature Compensated Crystal Oscillator YSO510TP TCXO




Applications

- Networking
- Industrial

Features

- Frequency Stability as Tight as ± 1.0 ppm Over -40°C to 85°C
- Package Size : 2.0*1.6, 2.5*2.0, 3.2*2.5, 5.0*3.2, 7.0*5.0mm
- Ultra Small SMD Seam Sealed Crystal Oscillator



Specifications (规格参数)

Item/Type			Clipped Sine Wave or CMOS				
Package Size 封装尺寸			2.0 x 1.6	2.5 x 2.0	3.2 x 2.5	5.0 x 3.2	7.0 x 5.0
Frequency Range 额定频率范围			26 ~ 52MHz	13 ~ 52MHz	13 ~ 52MHz	6.4 ~ 52MHz	6.4 ~ 52MHz
Supply Voltage 电源电压			1.8V, 2.5V, 3V, 3.3V				
Operating Temperature Range 工作温度			-30 ~ +85°C, or specify				
Storage Temperature Range 储存温度			-40°C to +85°C				
Output Type 输出方式			Clipped Sine wave or CMOS				
Current Consumption (max.) 消耗电流			Clipped Sine Wave: 3.5mA (Max) CMOS: 1.8V/2.5V:10mA (Max); 3V/3.3V:13mA (Max)				
Duty Cycle 占空比			40~60%				
Output Voltage Level (peak to peak) 峰峰值			Clipped Sine Wave: 0.8 Vp-p Min. CMOS: VOH = 80%Vdd(Min.)/VOL = 20%Vdd(Max.)				
Start-up Time 启动时间			2.0msec(Typ.), 5.0msec(Max.) @+25±2°C				
Initial Calibration Tolerance 初始校准公差			±2.0 ppm (Max.) at +25°C±2°C (at the shipment)				
Output Load 输出负载			Clipped Sine Wave: 10KΩ // 10pF ± 10% CMOS: 15pF				
Frequency Stability 频率偏差	vs Aging at Ta = +25°C		± 1.0 ppm / year (Max.)				
	vs Voltage Change		± 0.2 ppm (Max.) , for a ±5% input voltage change				
	vs Load Change		± 0.2 ppm (Max.) , for a ±10% load condition change				
	vs Reflow		± 2.5 ppm (Max.)				
	vs Temperature Change		5ppm / ±2.5ppm				
Phase Noise [dBc / Hz ; (typ.)] 相位噪声	Offset	10 Hz	100 Hz	1 KHz	10 KHz	100 KHz	
	13.0 MHz	-80 (max)	-115	-135	-148	-148(Min)	


Temperature Compensated Crystal Oscillator YSO510TP TCXO



Pin Description-CMOS (脚位说明-CMOS)

Pin	#1	#2	#3	#4
Function	Output Enable	Ground	Output	Supply Voltage


Pin Assignments-CMOS



Pin Description-Clipped sine wave (脚位说明-Clipped sine wave)

Pin	#1	#2	#3	#4
Function	No Connect	Ground	Output	Supply Voltage

Pin Assignments-Clipped sine wave



Notes:

1. Please keep the NC pin floating during use. Do not connect it to any network (power, ground, or signal).
2. The provided pinout is for reference purposes only. The definitive material specification document must be obtained by contacting a sales representative.




Dimensions and Recommended Land Pattern (外观尺寸及推荐焊盘)

Dimensions (Unit: mm)	Recommended Land Pattern (Unit: mm)
2.0*1.6mm Top View Bottom View Side View	Recommended soldering Pattern

Temperature Compensated Crystal Oscillator YSO510TP TCXO






2.5*2.0mm






Recommended soldering Pattern

3.2*2.5mm



Recommended soldering Pattern

5.0*3.2mm





Recommended soldering Pattern

Temperature Compensated Crystal Oscillator YSO510TP TCXO



7.0*5.0mm





Recommended soldering Pattern

Notes:

1. A capacitor of value 0.01uF~0.1uF or higher between Vdd and GND is required.
2. The dimensions are for reference purposes only. The definitive material specification document must be obtained by contacting a sales representative.

Output Waveform and Test Circuit (输出波形和测试电路)

CMOS



Clipped Sine Wave

